
SPECIFICATIONS

HARDWARE

Cabinet Construction	1.2mm Mild Steel
Dimensions	335mm x 260mm x 80mm
Weight (No Battery)	3.2 kg
Transformer Rating	18V 1.4A
Bridge Diode Rating	3A
Power Supply Rating	1.2A
Quiescent Current Draw	180mA - With 1 Keypad
Operating Voltage	10-14V d.c.
Recommended Battery	12 Vol 6.6 A / Hr
Battery Charge Voltage	13.8V d.c.
Battery Charge Current Limit	350mA
Dynamic Battery Test	5A load
Protective Fuses	1A Fast
Zone Inputs	8 Balanced
End-of-line Resistor value	2k2
Zone Input Filtering	R/C
Tamper Input	2k2
Keyswitch Input	2k2
Remote Keypad ports	2
Maximum Keypads	6 (3 per Port)
Output Relay	1A change over
High Current Outputs	2 @ 1.5A
Additional Definable Outputs	6 @ 100mA
Dynamic Power-off Reset	Yes
External equipment Supply	1.02A

SOFTWARE

Max User Codes	15
Installer Codes	1
Code Length	3-6 Digit
Available Zone Types	10
Zone Auto Exclude	Selectable
Dialler Indications Available	10
Smoke Reset	1
2 Trigger Window	1-99 Sec
Alarm Memory	20 Events
Dialler Format	Ademco Contact ID
Dialler Event Buffer	16 Events
Radio Zones	8 Max